

PolyPlus

rev. o

in Home Appliance Serial Production



DISPENSER BODY IN PP 30% TALC FILLED 250 TONN INJECTION MACHINE CYCLE WITHOUT POLY PLUS 45,8 SEC CYCLE TIME WITH POLY PLUS 25 SEC



photos only for didactical using not be distributed without permission of Keytech



TOP FRAME WASHING MACHINE 600 TONN INJECTION MACHINE MATERIAL ABS CYCLE TIME WITHOUT POLY PLUS 40 SEC CYCLE TIME WITH POLY PLUS 23 SEC



photos only for didactical using not be distributed without permission of Keytech RUNNING PRODUCTION
42% CICLE TIME SAVING






door handle
4-cavity mould.
200 tonn Injection Machine.
Material PP 30% Calcium Carbonate.
Standard Cycle 26 second.
With Poly Plus new cycle 18 seconds

photos only for didactical using not be distributed without permission of Keytech RUNNING PRODUCTION 30% CICLE TIME SAVING






Refrigerator Drawer
2-cavity mould.
420 grams
650 tonn Injection Machine.
Material PP 30% Calcium Carbonate.
Standard Cycle 52 second.
With Poly Plus new cycle 36,5 seconds

photos only for didactical using not be distributed without permission of Keytech RUNNING PRODUCTION
30% CICLE TIME REDUCTION





Refrigerator balcony storage
2-cavity mould.
200 grams
550 tonn Injection Machine.
Material PS White.
Standard Cycle 42 second.
With Poly Plus new cycle 31,5 seconds

photos only for didactical using not be distributed without permission of Keytech RUNNING PRODUCTION
25% CICLE TIME REDUCTION





Valve Body 180°
1-cavity mold.
65 grams
150 tonn Injection Machine.
Material PA66 30% GF hydrolysis resistant
Standard Cycle 33 second.
With Poly Plus new cycle 25 seconds

photos only for didactical using not be distributed without permission of Keytech **RUNNING PRODUCTION 25% CICLE TIME SAVING**





Separator
2-cavity mold.
48 grams
250 tonn Injection Machine.
Material HDPE
Standard Cycle 41 second.
With Poly Plus new cycle 27 seconds

photos only for didactical using not be distributed without permission of Keytech RUNNING PRODUCTION 34% CICLE TIME SAVING